

## Bard Information Center

50HZ Air Conditioners (Export)

The Wall-Mount™:	
<b><u>9,500 BTUH Units</u></b>	<b><u>21,300-60,000 BTUH Units</u></b>

### **50HZ Air Conditioner Technical Information**

For additional Information:

Leon Schorr

International Sales Manager

T: (USA): 561.734.3836

F: (USA): 561.374.9345

**[bardintl@adelphia.net](mailto:bardintl@adelphia.net)**

#### The Wall-Mount™ 9,500 Btuh ~ 50 HZ Air Conditioners



- Rotary Compressor
- Aluminum Fin/Copper Coils
- High Pressure Control
- Full Length Mounting Brackets
- Built-in Rain Hood/Top Rain Flashing
- Barometric Fresh Air Damper
- Optional Telecommunication "J" Control Module
- Limited Warranty Policy

**[Wall-Mount™ 9500 Btuh Air Conditioner Technical Information Link](#)**

WA Series Wall-Mount™ Air Conditioners	
Cooling Capacities <sup>1</sup>	9,500 BTUH / 2.78 KW
Electrical Options	WA Series (R-22 Refrigerant) 220-1-50hz

	WE Series (R407C Refrigerant) 220-1-50hz
Cooling Efficiency	9.5 EER <sup>2</sup>
Electric Heat Options	Range from 0 KW to 03 KW
Ventilation Options	<ul style="list-style-type: none"> <li>• Barometric Fresh Air Damper</li> <li>• Blank Off Plate</li> <li>• Economizer</li> </ul>
Internal Control Options	<ul style="list-style-type: none"> <li>• High Pressure Control and Compressor Control Module (Standard)</li> <li>• Low Pressure Control</li> <li>• Low Ambient Control</li> <li>• Alarm Relay</li> </ul>

[Top of page.](#)

#### The Wall-Mount™ - 50 HZ Air Conditioners



- Aluminum Fin/Copper Coils
- Circuit Breaker/Toggle disconnect on all KW and 0Z Models
- Full Length Mounting Brackets
- Built-in Rain Hood/Top Rain Flashing
- Barometric Fresh Air Damper
- Optional Ventilation & Controls Available
- Left-Hand Service Access Available on WL602-F units for Telecommunication Shelter Applications
- Hot-Gas By-Pass Option Available on WA361-F, WA484-F and WA602-F Models

[Wall-Mount™ 21,300-60,000 Btuh Air Conditioner Technical Information Link](#)

Capacities <sup>1</sup>	BTUH
Electrical Options	WA Series - (R22 Refrigerant) 240/220-1-50hz ~ 220/200-3-50hz ~ 415/380-3-50hz
	WE Series (R407C "Green" Refrigerant) 240/220-1-50hz ~ 415/380-3-50hz
Electric Heat Options	Range from 0 KW to 14 KW
Ventilation Options	<ul style="list-style-type: none"> <li>• Barometric Fresh Air Damper</li> <li>• Blank Off Plate</li> <li>• Motorized Fresh Air Damper</li> <li>• Commercial Room Ventilator</li> <li>• Economizer</li> </ul>
Internal Control Options	<ul style="list-style-type: none"> <li>• High &amp; Low Pressure Switch</li> <li>• Low Ambient Control</li> <li>• Time Delay Relay</li> <li>• Alarm Relay</li> <li>• Start Kit</li> </ul>
Specified Applications	<ul style="list-style-type: none"> <li>• Telecom Wall Curb Option</li> <li>• Technicoat Coil Coatings For Corrosive Environments Options</li> </ul>

**Top of page.**

1. Capacity is certified in accordance with ARI Standard 390-2003 and tested in accordance with ARI Standard 210/240-2003.
2. EER = Energy Efficiency Ration and is certified in accordance with ARI Standard 390-2003.
3. SEER = Seasonal Energy Efficiency Ratio and is tested in accordance with ARI Standard 210/240-2003.



© 2005-2006 Bard Manufacturing Company, Inc.