Wall-MountTM Air Conditioners, 1 Ton

- Rotary Compressor •
- Aluminum Fin/Copper Coils •
- High Pressure Control •
- Full Length Mounting Brackets
- Built-in Rain Hood/Top Rain Flashing
- Barometric Fresh Air Damper •
- **ARI** Certified •
- UL & CUL (Canadian) Listed •
- Optional Telecommunication Control Module J •
- Limited Warranty Policy •

1 Ton Wall-Mount[™] Air Conditioner Technical Information Link

1 Ton Series Wall-Mount TM Air Conditioners	
Nominal Cooling Capacities ¹	11,100 BTUH
Electrical Options	• 115-60-1 • 230/208-1-60
Electric Cooling Efficiency	9.0 EER ² 10.00 SEER ³
Electric Heat Options	Ranges from 0 KW to 5 KW
Ventilation Options	 Barometric Fresh Air Damper Blank Off Plate Economizer
Internal Control Options	 High & Low Pressure Switch Compressor Time Delay Relay Low Ambient Control Alarm Relay

- 1. Capacity is certified in accordance with ARI Standard 390-2003 and tested in accordance with ARI Standard 210/240-2003.
- 2. EER = Energy Efficiency Ration and is certifed in accordance with ARI Standard 390-2003.
- 3. SEER = Seasonal Energy Efficiency Ratio and is tested in accordance with ARI Standard 210/240-2003.



© 2005-2006 Bard Manufacturing Company, Inc.

