

Wall-Mount™ Air Conditioners, 1.5 - 5 Ton

- Aluminum Fin/Copper Coils
- Circuit Breaker/Toggle disconnect on all KW and OZ Models
- High Pressure Control - 4 & 5 Ton Models
- Full Length Mounting Brackets
- Built-in Rain Hood/Top Rain Flashing
- Barometric Fresh Air Damper
- ARI Certified
- UL & CUL (Canadian) Listed
- Optional Ventilation & Controls Available
- Limited Warranty Policy



[1.5 - 5 Ton Wall-Mount™ Air Conditioner Technical Information Link](#)

WA Series Wall-Mount™ Air Conditioners	
Nominal Cooling Capacities ¹	Ranges from 1.5 to 5.0 Tons
Electrical Options	<ul style="list-style-type: none"> • 230/208-1-60 • 230/208-3-60 • 460-3-60
Cooling Efficiency	8.7 EER to 11.3 EER ² 10.0 SEER - 12.5 SEER ³
Electric Heat Options	Ranges from 0 KW to 20 KW
Ventilation Options	<ul style="list-style-type: none"> • Barometric Fresh Air Damper • Blank Off Plate • Motorized Fresh Air Damper • Commercial Room Ventilator • Economizer • Energy Recovery Ventilator
Internal Control Options	<ul style="list-style-type: none"> • High & Low Pressure Switch • Compressor Time Delay Relay • Low Ambient Control • Outdoor Thermostat • Start Kit • Alarm Relay • Telecom DDC Sensors

1. Capacity is certified in accordance with ARI Standard 390-2003 and tested in accordance with ARI Standard 210/240-2003.
 2. EER = Energy Efficiency Ratio and is certified in accordance with ARI Standard 390-2003.
 3. SEER = Seasonal Energy Efficiency Ratio and is tested in accordance with ARI Standard 210/240-2003.

