

Product Information

High Performance Building

DOW CORNING

Dow Corning[®] 1299 Silicone Seam Sealer

FEATURES & BENEFITS

- Self leveling seam sealant that flows into joints without tooling
- Significantly less odor compared to solvent borne acrylic seam sealers
- Minimal shrinkage
- Low VOC (less than 60g/L)
Meets VOC requirements of SCAQMD Rule 1168

COMPOSITION

- One-part, neutral cure RTV silicone sealant

Self Leveling Silicone Sealant for use in seam or joinery applications of fenestration assemblies to reduce or prevent air and water infiltration.

APPLICATIONS

- Seam or joint sealer in construction of fenestration assemblies to prevent or reduce air or water infiltration between miter, fastened or slip-jointed extrusions
- Seals screw head, fasteners and end dams

TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales office or your Global Dow Corning Connection before writing specifications on this product.

Test	Property	Unit	Result
Uncured – As Tested at 23°C (75°F) and 50% RH			
ASTM D2377	Tack-Free Time	Minutes	25
ASTM C603	Extrusion Rate	Grams/minute	130
ASTM D2202 ¹	Slump	Inches (mm)	>0.3 (>7)
CTM ² 0663	Cure in Depth @ 24 hours	Inches (mm)	0.100 (2.5)
ASTM D1475	Specific Gravity		1.02
Cured – After 7 days at 23°C (75°F) and 50% RH			
ASTM C661	Durometer, Type A	points	19
ASTM D412	Tensile Strength	psi (kg/mm ²)	120
ASTM D412	Elongation	percent	300
ASTM D711	Temperature Range	°C (°F)	-40 to 149 (-40 to 300)

¹ As tested on the AAMA test jig as shown in section 2.6 in the AAMA 800 Voluntary Test Methods and Specifications

² CTM is an acronym for Corporate Test Methods of Dow Corning.

DESCRIPTION

Dow Corning[®] 1299 Silicone Seam Sealer is a one-part, neutral-cure RTV sealant specifically formulated to meet the demanding requirements as a self-leveling seam sealer for fenestration assemblies. It is designed for durable performance and aggressive adhesion to many common fenestration substrates.

HOW TO USE

Preparation

Clean and dry surfaces before sealant application.

Application

Apply materials from cartridges using standard one-component pumping and dispensing equipment.

Dow Corning 1299 Silicone Seam Sealant is available in clear.

**HANDLING
PRECAUTIONS
PRODUCT SAFETY
INFORMATION REQUIRED FOR
SAFE USE IS NOT INCLUDED IN
THIS DOCUMENT. BEFORE
HANDLING, READ PRODUCT
AND MATERIAL SAFETY DATA
SHEETS AND CONTAINER
LABELS FOR SAFE USE,
PHYSICAL AND HEALTH
HAZARD INFORMATION. THE
MATERIAL SAFETY DATA
SHEET IS AVAILABLE ON THE
DOW CORNING WEB SITE AT
DOW CORNING.COM, OR FROM
YOUR DOW CORNING SALES
APPLICATION ENGINEER, OR
DISTRIBUTOR, OR BY CALLING
DOW CORNING CUSTOMER
SERVICE.**

USABLE LIFE AND STORAGE

When stored in original, unopened containers in a dry location below 32°C (90°F), *Dow Corning* 1299 Silicone Seam Sealer has a usable life of 12 months from date of manufacture. Refer to product packaging for "Use By" date

PACKAGING INFORMATION

Dow Corning 1299 Silicone Seam Sealer is available in 10.3-fl oz (305-mL) cartridges and 200 kg drums.

LIMITATIONS

Dow Corning 1299 Silicone Seam Sealer is not intended for use:

- In spaces totally confined from atmospheric moisture during cure
- In silicone structural glazing applications
- As an insulating glass (IG) sealant
- On surfaces that will require painting or staining
- On frost-laden or wet surfaces

- In areas where abrasion and physical abuse are encountered
- Continuous water immersion

Dow Corning® 1299 Silicone Seam Sealer may stress crack polycarbonate

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

HEALTH AND ENVIRONMENTAL INFORMATION

To support Customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Product Safety and Regulatory Compliance (PS&RC) specialists available in each area.

For further information, please see our Web site, dowcorning.com or consult your local Dow Corning representative.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

**DOW CORNING SPECIFICALLY
DISCLAIMS ANY OTHER
EXPRESS OR IMPLIED
WARRANTY OF FITNESS FOR A
PARTICULAR PURPOSE OR
MERCHANTABILITY.**

**DOW CORNING DISCLAIMS
LIABILITY FOR ANY
INCIDENTAL OR
CONSEQUENTIAL DAMAGES.**

We help you invent the future.™

dowcorning.com

Aug 2, 2013

